



# **CleanUnit MSV1**

# Media supply cabinet for interior cleaning facilities



## **CleanUnit MSV1**

## Media supply cabinet for interior cleaning facilities

The Vogelsang cleaning cabinet series CleanUnit MSV complements interior cleaning facility infrastructures in train care depots or other public transport facilities ideally.

The cabinet is made entirely from durable, stainless steel material.

The CleanUnit is equipped with the required cleaner facilities including a stainless steel sink and media taps.

The highlycompact design of the CleanUnit enables installation even where space is very limited.

On request the cabinet can be fitted with a compartment for storing cleaning equipment and typical sanitation products.

Heating elements ensure availability even at low outside temperatures.

The CleanUnit also includes an electrical combination socket for connecting external cleaning devices.

## Advantages

- Decentralized cleaner supply station
- Cabinet in stainless steel design
- Valves and fittings mounted behind a protective cover
- Convenient local hot & cold water supply with scald protection
- Antifreeze heating enables outdoor operation
- Upgradeable combination socket

### Options

- Storage compartment for storage of cleaning equipment
- Instantaneous water heater
- 3.5 kW 230 V 50 Hz, capacity approx.: 1.7 l/min\*
- Trace heater for water provided in the base
- Electrical socket combination:
  - CEE socket 3x 400 V 16 A IP44
- Insulated support for height adjustment between foundation and elevated platforms
- Locking system: key cylinders
- Mounting frame for cast-in-place foundations or prefabricated one-piece foundation base
- Additional thermal insulation for ambient temperatures as low as -25 °C





#### Standard specifications

Cabinet design	Stainless steel (SS304)
Sink compartment	Stainless steel sink with grating & media taps
Electrical sub- distribution	Iso-distribution board 3-400 V, 50 Hz IP54, Protection class II Cable grommet: max. Ø16 mm²
Combination socket	1x Schuko CEE7/3 IP44 1-230 V, 50 Hz, 16 A
Water heater	Small 5 l. storage water heater Rated power: 2.0 kW, 230 V, 50 Hz Capacity: 30 l/h*
Heating elements	1x 250 W
Door locks	Square socket key 8 mm
Main dimensions LxWxH approx.	700 x 260 x 1500 mm
Weight approx.	100 kg
Ambient temperatures	-20 to +40°C
Ambient conditions	Moderate

\*Average capacity allowing a temperature increase of  $\Delta T \approx$  +30 °C (e.g. +5 up to +35 °C)